

ATV 4T Motoroil SAE 5W-50**Description**

Fully synthetic high-performance motor oil, developed and tested on racing machines. Ensures maximum performance and protection even in extreme operating conditions. Provides maximum engine cleanliness, reduced friction and minimum wear with smooth clutch operation, and effortless gear shift resulting in complete riding satisfaction!

Properties

- high lubrication reliability
- high wear resistance
- ideal with catalytic converters
- outstanding engine cleanliness
- optimum oil pressure under all operating conditions
- instant lubrication after cold start

Approvals

API SN PLUS • JASO MA2

Technical data

SAE class (engine oils)	5W-50 SAE J300
Density at 59 °F	0,85 g/cm ³ DIN 51757
Viscosity at 104 °F	105 mm ² /s ASTM D 7042-04
Viscosity at 212°F	17,3 mm ² /s ASTM D 7042-04
Viscosity at -31 °F (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -22 °F (CCS)	<= 6600 mPas ASTM D 5293
Viscosity index	180 DIN ISO 2909
HTHS at 302 °F	>= 3,7 mPas ASTM D 5481
Pour point	-38 °F DIN ISO 3016
Evaporation loss (Noack)	12 % CEC-L-40-A-93
Flash point	446 °F DIN ISO 2592
Total base number	7 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049

**Areas of application**

For 4-stroke gasoline engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.

Available pack sizes

1 l Canister plastic	20212 USA-AND-CANADA-EN-F
4 l Canister plastic	20214 USA-AND-CANADA-EN-F
4 l Canister plastic	20738 BOOKLET

Our information is based on thorough research and may be considered reliable, although not legally binding.